



DOKUNMATIK FKRAN CAMI ARI

TOUCH FRAME KEETOUCH 60" KP-600-IPOS001

FLEXIBLE SIZE

Impact-resistant Infrared steel touch frames are an ideal solution for large touch surfaces of unlimited sizes. The size range is their key advantage. It's possible to produce small size screens starting from 10inch as well as the frames of nearly unlimited sizes up to 98". Infrared touch frames are used wherever high-definition and colorful image is required. They are perfect for presentations, commercials and digital signage as well as educational institutions. MultiTOUCH

Supports 2 to 40 touch points (optional). Double-touch interface supports scaling, zooming and image rotating. Learn more on installing the touch technology software drivers for IR devices.

INFRARED TOUCH TECHNOLOGY

No pressure required: responses to a quick light touch of any object.

UYGULAMA

GAMING / CASINO SYSTEMS

OUTDOOR AND INDOOR KIOSKS

ENTERTAINMENT

TRANSPORT AND TICKETING

HOSPITALITY

BANKING

CUSTOMIZED SOLUTIONS





SPLIETERSTRASSE 61, WARENDORF
DEUTSCHLAND, 48231
+49 (0) 25 8161 04089
ENQUIRIES@KEETOUCH.EU



LINKEDIN.COM/COMPANY/KEETOUCH-EU



FACEBOOK.COM/KEETOUCH





SPECIFICATION *

Mode	$\overline{}$

Model	KP-600-IP0S001	
Dokunmatik Ekran Tipi	Frame	
Display characteristics		
Dokunmatik Ekran Tipi	Infrared	
Diyagonal	60"	
En boy oranı	16:9	
Aktif alan (G*Y)	1333,9 mm × 749,8 mm	
Ekran genişliği	1371,9 mm	
Ekran yüksekliği	787,8 mm	
Ekran kalınlığı	9 mm	
Cam malzeme	Aluminium alloy metal frame (with 3 mm tempered glass optional)	
Surface hardness	_	
Saydamlık	100% (92% with glass)	
Desteklenen dokunma sayısı	2 – 40 (optional)	
Yanıt nesnesi	Any 3 and higher mm thick object	
Tepki süresi	32 ms	
Interfaces		
Dokunmatik arayüzü	USB	
Environment		
Çalışma sıcaklığı	0+50 °C (-20+70 °C optional)	
Depolama sıcaklığı	-30+60 °C (-30+70 °C optional)	
Çalışma nemi	20% – 85%	
Depolama nem	20% – 85%	
Power management		
Güç kaynağı	USB	
Güç tüketimi	Max. 0,8 W	
Additional Features		
İşletim sistemiDesteklenen işletim sistemi	Windows 7 and higher, Linux (core 3.0 and higher)	

^{*} some factory modifications can be made

Drawing is missing

