KeeTouch
TOUCHMONITORS & TOUCHSCREENS




TOUCH SCREENS


TOUCH SCREEN KEETOUCH 30"
KP-300-SW0S0U1

Single-TOUCH
Surface Acoustic Wave single-touch screens with protective frame are perfect for step-by-step use. Convenient single-touch technology prevents accidental touches:
While running production lines
While interacting with the Human Machine Interface (HMI)
While entering a password at security checkpoints
While entering data through payment terminals and ATMs
Single-touch support allows working with non-adapted Windows software: no reinstallation of the software is needed for touchscreen equipment.
Optional double-touch makes gesture control possible: scroll, swipe, zoom and scale. Learn more on installing the touch technology software drivers for SAW devices.
ANTIVANDAL TECHNOLOGIES
Shock-resistant tempered glass with a 4-6 mm thickness and a 7H hardness is almost impossible to break accidentally.

APPLICATION

GAMING / CASINO SYSTEMS
OUTDOOR AND INDOOR KIOSKS
ENTERTAINMENT
TRANSPORT AND TICKETING
HOSPITALITY
BANKING
CUSTOMIZED SOLUTIONS







SPLIETERSTRASSE 61, WARENDORF
DEUTSCHLAND, 48231
+49 (0) 25 8161 04089
ENQUIRIES@KEETOUCH.EU

LINKEDIN.COM/COMPANY/KEETOUCH-EU
FACEBOOK.COM/KEETOUCH

WWW.KEETOUCH.EU

SPECIFICATION *

Model	
Model	KP-300-SW0S0U1
Touch screen type	Touch screen with frame
Screen Features	
Touch technology	SAW (Surface Acoustic Wave)
Diagonal	30"
Aspect ratio	16:10
Active area (W × H)	640 × 400 mm
Screen width	678 mm
Screen height	436 mm
Screen thickness	4 – 6 mm (optional)
Screen material	Glass
Surface hardness	7H
Transparency	90%
Touch points	1
Response object	Finger
Response time	10 ms
Interfaces	
Touch screen In	USB
Environment	
Working temperature	-20...+60 °C
Storage temperature	-40...+70 °C
Working humidity	20% – 90%
Storage humidity	20% – 90%
Power management	
Power source	USB
Power consumption	Max 0,6 W
Additional Features	
Compatibility with OS	Windows XP, Windows 7 and higher, Linux (core 3.0 and higher)

* some factory modifications can be made