



Keetouch embedded monitor is a perfect solution for your project.

Industrial monitor Keetouch 19" Open Frame KOM-0190-6PS is designed specifically for easy integration in various types of equipment. It has a long-lasting operation.

The monitor has an option for horizontal mounting. A solid framework and durable glass serve as a protection for the LCD screen from mechanical impact. The front panel of the monitor is protected from dust contamination.

- GAMING / CASINO SYSTEMS
- OUTDOOR AND INDOOR KIOSKS
- ENTERTAINMENT
- TRANSPORT AND TICKETING
- HOSPITALITY
- BANKING
- CUSTOMIZED SOLUTIONS



SPECIFICATION *

Model	
Model	KOM-0190-6PS
Series	Dust-proof (front panel)
Monitor type	Open Frame
Display characteristics	
Diagonal	19"
Aspect ratio	5:4
Display type	Active matrix TFT-LCD
Active area (W × H)	376 × 301 mm
Monitor width	416 mm
Monitor height	344 mm
Monitor depth	54 mm
Resolution	1280×1024
Colors	16.7 million
Brightness	250 cd/m²
Viewing angle (H)	Left 85° / right 85°
Viewing angle (V)	Up 80° / down 80°
Contrast	1000:1
Frequency (H / V)	30 – 80 KHz / 60 – 75 Hz
Interfaces	
Digital video In	DVI
Analog video in	VGA
Power management	
Power source	External power brick
Input voltage	12 V, 4 A
Power consumption	Max. 16.47 W
Environment	
Working temperature	0...+50 °C
Storage temperature	-20...+60 °C
Working humidity	20% – 80%
Storage humidity	10% – 90%
Additional Features	
Mounting VESA sizes	75 mm and 100 mm
Mounting options	Horizontal or vertical mounting holes
On-screen display function	Auto-Adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Buttons	AUTO, +, POWER, -, MENU

* some factory modifications can be made

